

Safety Data Sheet

according to Regulation (EC) No. 453/2010 Date of issue: 30/01/2014 Revision date: 20/02/2015

)/02/2015 Super

Supersedes: 30/01/2014

Version: 1.1

	e substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	
Product name	: ENEOS Premium Hyper R1 5W-30
Product code	: V161500032
Product group	: Trade product
1.2. Relevant identified uses of th	e substance or mixture and uses advised against
1.2.1. Relevant identified uses	
Intended for general public	
Main use category	: industrial use, professional use, consumer use
Use of the substance/mixture	: Lubricant
Function or use category	: Lubricants and additives
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier of the s	-
JX NIPPON OIL & ENERGY EUROPE LI 4th Floor, 4 Moorgate	
London, EC2R 6DA	
UNITED KINGDOM	
1.4. Emergency telephone numbe	pr
Emergency number	: 0044 20 7186 0400
0	(Monday to Friday: 8:00 - 17:00)
SECTION 2: Hazards identificat	tion
2.1. Classification of the substand	ce or mixture
2.1. Classification of the substance Classification according to Regulation Not classified	
Classification according to Regulation Not classified Classification according to Directive 67	(EC) No. 1272/2008 [CLP]
Classification according to Regulation	(EC) No. 1272/2008 [CLP]
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements	(EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD]
Classification according to Regulation Not classified Classification according to Directive 67 Not classified	(EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD]
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP)	(EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD]) No. 1272/2008 [CLP] : P102 - Keep out of reach of children
Classification according to Regulation Not classified Classification according to Directive 63 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce allergic reaction
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements 2.3. Other hazards	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce allergic reaction EUH210 - Safety data sheet available on request
Classification according to Regulation Not classified Classification according to Directive 63 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce allergic reaction EUH210 - Safety data sheet available on request This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classifi as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cance
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements 2.3. Other hazards Dther hazards not contributing to the classification	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce allergic reaction EUH210 - Safety data sheet available on request This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classifia as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements 2.3. Other hazards Other hazards not contributing to the classification SECTION 3: Composition/inform	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce allergic reaction EUH210 - Safety data sheet available on request This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classifia as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements 2.3. Other hazards Other hazards not contributing to the classification SECTION 3: Composition/inform	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce a allergic reaction EUH210 - Safety data sheet available on request This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classifia as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Classification according to Regulation Not classified Classification according to Directive 67 Not classified 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements 2.3. Other hazards Other hazards not contributing to the classification SECTION 3: Composition/inform 3.1. Substance	 (EC) No. 1272/2008 [CLP] 7/548/EEC [DSD] or 1999/45/EC [DPD] No. 1272/2008 [CLP] P102 - Keep out of reach of children EUH208 - Contains 1H-1,2,4-Triazole-1-methanamine, N,N-bis(2-ethylhexyl) May produce allergic reaction EUH210 - Safety data sheet available on request This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classifi as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cance Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS No) 64742-54-7 (EC no) 265-157-1 (EC index no) 649-467-00-8 (REACH-no) 01- 2119484627-25	35 - 50	Not classified	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	(CAS No) 72623-87-1 (EC no) 276-738-4 (EC index no) 6494-483-00- 5 (REACH-no) 01- 2119474889-13	25 - 35	Not classified	Asp. Tox. 1, H304
Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched)	(CAS No) 36878-20-3 (EC no) 253-249-4 (REACH-no) 01- 2119488911-28	2,5 - 5	R53	Aquatic Chronic 4, H413
Minerale olie		2,5 - 5	Not classified	Asp. Tox. 1, H304

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medica advice. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
First-aid measures after ingestion	: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.
4.2. Most important symptoms and ef	fects, both acute and delayed
Symptoms/injuries after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumer resulting from thermal decomposition products occurs.
Symptoms/injuries after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/injuries after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/injuries after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/injuries upon intravenous administration	: Unknown.
4.3. Indication of any immediate medi	cal attention and special treatment needed
Treat compationally	

Treat symptomatically.

SECTION 5: Firefighting measures	3
5.1. Extinguishing media	
Suitable extinguishing media	: Carbon dioxide (CO2), dry chemical powder, foam. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.
5.2. Special hazards arising from the	substance or mixture
Fire hazard	: Combustion generates : CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.
5.3. Advice for firefighters	
Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: Prevent fire-fighting water from entering environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 6: Accidental release r	measures
6.1. Personal precautions, protectiv	ve equipment and emergency procedures
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
6.1.1. For non-emergency personnel	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Consider evacuation.
6.1.2. For emergency responders	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.
6.2. Environmental precautions	
	e material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. courses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and
6.3. Methods and material for conta	ainment and cleaning up
For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pou out in disposal container.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and store	
SECTION 7: Handling and storage	je
7.1. Precautions for safe handling	
	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
7.1. Precautions for safe handling	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned
7.1. Precautions for safe handling Additional hazards when processed	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during
7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, interview	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions Incompatible products 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions Incompatible products Maximum storage period 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, interpretation Technical measures Storage conditions Incompatible products 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions Incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year ≤ 40 °C.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions Incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage Storage area 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year ≤ 40 °C. Keep away from : oxidizing materials. strong acids.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, im Technical measures Storage conditions Incompatible products Maximum storage period Storage temperature 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Keep away from : oxidizing materials. strong acids. Store at ambient temperature.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, incompatible products Storage conditions Incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage Storage area Special rules on packaging 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Keep away from : oxidizing materials. strong acids. Store at ambient temperature.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions Incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage Storage area Special rules on packaging 7.3. Specific end use(s) No additional information available 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year ≤ 40 °C. Keep away from : oxidizing materials. strong acids. Store at ambient temperature. Keep container tightly closed and dry.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage Storage area Special rules on packaging 7.3. Specific end use(s) No additional information available SECTION 8: Exposure controls/page 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year ≤ 40 °C. Keep away from : oxidizing materials. strong acids. Store at ambient temperature. Keep container tightly closed and dry.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, in Technical measures Storage conditions Incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage Storage area Special rules on packaging 7.3. Specific end use(s) No additional information available SECTION 8: Exposure controls/ 8.1. Control parameters 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year ≤ 40 °C. Keep away from : oxidizing materials. strong acids. Store at ambient temperature. Keep container tightly closed and dry.
 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, interpret Technical measures Storage conditions Incompatible products Maximum storage period Storage temperature Prohibitions on mixed storage Storage area Special rules on packaging 7.3. Specific end use(s) No additional information available SECTION 8: Exposure controls/ 8.1. Control parameters 	 Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cluding any incompatibilities Keep container tightly closed and in well ventilated place. Store in original container. Reacts vigorously with strong oxidizers and acids. 5 year ≤ 40 °C. Keep away from : oxidizing materials. strong acids. Store at ambient temperature. Keep container tightly closed and dry.

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

Safety Data Sheet

according to Regulation (EC) No. 453/2010

8.2. Exposure controls	
Appropriate engineering controls	: Large quantities: Contain large spillage with sand or earth.
Personal protective equipment	: Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.
Materials for protective clothing	: PVC gloves. Neoprene or nitrile rubber gloves
Hand protection	In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
Eye protection	: Eye protection should only be necessary where liquid could be splashed or sprayed
Skin and body protection	 No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.
Respiratory protection	: Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.
Environmental exposure controls	: See Heading 12. See Heading 6.
Consumer exposure controls	: PVC gloves. Neoprene or nitrile rubber gloves.

Other information

- : PVC gloves. Neoprene or nitrile rubber gloves.
- : Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemica	properties	
9.1. Information on basic physical and	chemical properties	
Physical state	: liquid	
Appearance	: Oily. liquid.	
Colour	: Brown.	
Odour	: characteristic.	
Odour threshold	: no data available	
рН	: no data available	
Relative evaporation rate (butylacetate=1)	: <0,1	
Melting point	: <= -39 °C.	
Freezing point	: no data available	
Boiling point	: > 280 °C.	
Flash point	: 233 °C.	
Auto-ignition temperature	: > 240 °C.	
Decomposition temperature	: no data available	
Flammability (solid, gas)	: no data available	
Vapour Pressure 20°C	: < 0,1 hPa	
Relative vapour density at 20 °C	: >1 (air=1)	
Relative density	: no data available	
Density	: 0,845 - 0,855 kg/l	
Solubility	: insoluble in water.	
Log Pow	: >3	
Viscosity, kinematic	: 150 - 300 cSt	
Viscosity, dynamic	: no data available	
Explosive properties	: no data available	
Oxidising properties	: no data available	
26/05/2015	EN (English) 4	/8

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Explosive limits	: 0,6 - 7 vol %	
9.2. Other	rinformation	
VOC content	: 0 %	
Other properties	: Gas/vapour heavier than air a	at 20'C.

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. strong acids.

10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity	: Not classified (Based on available data, the classification criteria are not met)		
Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)			

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 ml/kg (OECD 402 method)
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 5,53 mg/l
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: The mixture contains a substance with skin sensitization potential, but allergic skin reactions are not expected.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
ENEOS Premium Hyper R1 5W-30	
Viscosity, kinematic	150 - 300 mm²/s
Other information	: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.	
Ecology - water	This product floats on water and may affect the oxygen-balance in the water.	
Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)		
LC50 fish 1	> 100 mg/l 96h; Brachydanio rerio (zebra-fish)	
EC50 Daphnia 1	> 100 mg/l EC50 48h - Daphnia magna [mg/l]	
ErC50 (algae)	> 100 mg/l 72h; Desmodesmus subspicauts	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LC50 fish 1	100 mg/l	
26/05/2015	EN (English) 5/8	

ENEOS Premium Hyper R1 5W-30 Safety Data Sheet

ccording to Regulation (EC) No. 453/2010	
Distillates (petroleum), hydrotreated hear	
EC50 Daphnia 1	10000 mg/l
12.2. Persistence and degradability	
ENEOS Premium Hyper R1 5W-30	
Persistence and degradability	Not readily biodegradable.
,	nyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)
Biodegradation	0 % Sturm - 28 days
12.3. Bioaccumulative potential	
•	
ENEOS Premium Hyper R1 5W-30 Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
· ·	nyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)
Log Pow	> 7,6
Log Kow	7,3 Partition coefficient n-octanol/water [log Kow]
12.4. Mobility in soil	
ENEOS Premium Hyper R1 5W-30	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination.
	This product floats on water and may affect the oxygen-balance in the water.
12.5. Results of PBT and vPvB assess	ment
No additional information available	
12.6 Other educates effects	
12.6. Other adverse effects No additional information available	
SECTION 13: Disposal considerat	ions
13.1. Waste treatment methods	
Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code	: 13 02 06* - Synthetic engine, gear and lubricating oils
SECTION 14: Transport informatic	bn
In accordance with ADR / RID / IMDG / IATA	/ ADN
14.1. UN number	
Not regulated for transport	
14.2. UN proper shipping name	
Proper Shipping Name	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable
14.3. Transport hazard class(es) ADR	
Transport hazard class(es) (ADR)	: Not applicable
IMDG	
Transport hazard class(es) (IMDG)	: Not applicable
ΙΑΤΑ	
Transport hazard class(es) (IATA)	: Not applicable

Safety Data Sheet

according to Regulation (EC) No. 453/2010

ADN	
Transport hazard class(es) (ADN)	: Not applicable
RID	
Transport hazard class(es) (RID)	: Not applicable
14.4. Packing group	
Packing group (UN)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA) Packing group (ADN)	: Not applicable : Not applicable
Packing group (RID)	: Not applicable
14.5. Environmental hazards Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available
14.6. Special precautions for user	
- Overland transport	
no data available	
- Transport by sea	
no data available	
Air transport	
- Air transport no data available	
- Inland waterway transport	
Not subject to ADN	: No
- Rail transport	
Carriage prohibited (RID)	: No
14.7. Transport in bulk according to Ann	nex II of MARPOL 73/78 and the IBC Code
Not applicable	
SECTION 15: Regulatory informatio	n
15.1. Safety, health and environmental r	egulations/legislation specific for the substance or mixture
15.1.1. EU-Regulations	
Contains no substances with Annex XVII restric	tions
Contains no substance on the REACH candida	
Contains no REACH Annex XIV substances	
VOC content	: 0%
15.1.2. National regulations	
Germany	
VwVwS Annex reference	: Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS,
19th Ondinanaa Ingelang stilling the Earth.	Annex 4.)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen	:	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts,Phenol, dodecyl-, branched,Distillates (petroleum), hydrotreated heavy paraffinic are listed
SZW-lijst van mutagene stoffen	:	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts,Phenol, dodecyl-, branched,Distillates (petroleum), hydrotreated heavy paraffinic are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	:	None of the components are listed

Safety Data Sheet

according to Regulation (EC) No. 453/2010

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed
Denmark	
Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation	: Pregnant/breastfeeding women working with the product must not be in direct contact with the product
15.2. Chemical safety assessment	
No additional information available	

SECTION 16: Other information

Full text of R-, H- and EUH-statements:

Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways
H413	May cause long lasting harmful effects to aquatic life
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request
R53	May cause long-term adverse effects in the aquatic environment

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product