

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25/06/2014 Revision date: 08/01/2015 Supersedes: 25/06/2014

Version: 1.1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : ENEOS Premium Ultra S 0W-30

Product code : V161500025
Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1. Relevant identified uses

Intended for general public

Main use category : industrial use, professional use, consumer use

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

JX NIPPON OIL & ENERGY EUROPE LIMITED 4th Floor, 4 Moorgate London, EC2R 6DA UNITED KINGDOM

### 1.4. Emergency telephone number

Emergency number : 0044 20 7186 0400

(Monday to Friday: 8:00 - 17:00)

### SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children

EUH-statements : EUH208 - Contains Calcium long chain alkaryl sulfonate. May produce an allergic reaction

### 2.3. Other hazards

Other hazards not contributing to the

classification

: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substance

Not applicable

### 3.2. Mixture

30/09/2015 EN (English) 1/8

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS No) 64742-54-7 (EC no) 265-157-1 (EC index no) 649-467-00-8 (REACH-no) 01- 2119484627-25	35 - 50	Not classified	Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	(CAS No) 68037-01-4 (EC no) 500-183-1 (REACH-no) 01- 2119486452-34	25 - 35	Not classified	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50)		5 - 10	Not classified	Asp. Tox. 1, H304
Polyolefin polyamine succinimide, polyol		2,5 - 5	R53	Aquatic Chronic 4, H413
Polyolefin polyamine succinimide, borated		1 - 2,5	R53	Aquatic Chronic 4, H413

Full text of R- and H-statements: see section 16

	d measures

41	Description	of tiret aid	mageurae

First-aid measures general

First-aid measures after inhalation

: Seek medical attention if ill effect develops.

: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical

advice. Allow the victim to rest.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek

medical attention if ill effect or irritation develops.

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing
of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or

redness persist.

First-aid measures after ingestion

: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Symptoms/injuries after skin contact

: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Symptoms/injuries after eye contact Symptoms/injuries after ingestion Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
 Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger

quantities may cause nausea and diarrhoea.

Symptoms/injuries upon intravenous administration

: Unknown.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media

: Carbon dioxide (CO2), dry chemical powder, foam. Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard Explosion hazard : Combustion generates : CO, CO2, POx, NOx, SOx, H2S. Metallic oxides. : Not expected to be a fire/explosion hazard under normal conditions of use.

### 5.3. Advice for firefighters

Precautionary measures fire

: Do not enter fire area without proper protective equipment, including respiratory protection.

: Use water spray or fog for cooling exposed containers.

Protection during firefighting

: Use self-contained breathing apparatus and chemically protective clothing.

Other information

Firefighting instructions

: Prevent fire-fighting water from entering environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

30/09/2015 EN (English) 2/8

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public

6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of

splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be

required. Use protective clothing

Emergency procedures : Consider evacuation.

6.1.2. For emergency responders

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of

splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be

required.

**Emergency procedures** : No specific measures are necessary.

### **Environmental precautions**

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

### Methods and material for containment and cleaning up

For containment : Large quantities: Contain large spillage with sand or earth.

Methods for cleaning up : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Take up large spills with pump or vacuum and finish with dry chemical absorbent.

Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container Other information

for disposal in accordance with local regulations. On water, recover/skim from surface and pour

out in disposal container.

### Reference to other sections

For further information refer to section 13.

### **SECTION 7: Handling and storage**

### Precautions for safe handling

Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame,

sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned

to a drum reconditioner or disposed of properly.

Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where Precautions for safe handling

contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during

use. Remove contaminated clothing and shoes

Hygiene measures Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.

### Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.

Storage conditions Store in original container.

Reacts vigorously with strong oxidizers and acids. Incompatible products

Maximum storage period : 5 year Storage temperature : ≤ 40 °C

Prohibitions on mixed storage : Keep away from : oxidizing materials. strong acids.

: Store at ambient temperature. Storage area

Special rules on packaging : Keep container tightly closed and dry.

### Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Highly refined mineral oil (	C15 -C50)
------------------------------	-----------

ΕU IOELV TWA (mg/m3) 5 mg/m<sup>3</sup>

Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

30/09/2015 EN (English) 3/8

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2. Exposure controls

Appropriate engineering controls : Large quantities: Contain large spillage with sand or earth.

Personal protective equipment : Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary

where liquid could be splashed or sprayed.

Materials for protective clothing : PVC gloves. Neoprene or nitrile rubber gloves

Hand protection : In case of repeated or prolonged contact wear gloves. The gloves should be replaced

immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g.

mechanical strength, product compatibility, anti-static properties).

Eye protection : Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection : No special clothing/skin protection equipment is recommended under normal conditions of use.

Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing

is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection : Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be

checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product

temperature. Use filter type AP or comparable standard.





Environmental exposure controls : See Heading 12. See Heading 6.

Consumer exposure controls : PVC gloves. Neoprene or nitrile rubber gloves.

Other information : Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or

smoke during use. Wash contaminated clothing before reuse.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : liquid
Appearance : Oily. liquid.
Colour : Amber.
Odour : characteristic.
Odour threshold : no data available
pH : no data available

Relative evaporation rate (butylacetate=1) : < 0,1
Melting point : -48 °C

Freezing point : no data available

Boiling point :  $> 280 \, ^{\circ}\text{C}$ Flash point :  $202 \, ^{\circ}\text{C}$ Auto-ignition temperature :  $> 240 \, ^{\circ}\text{C}$ 

Decomposition temperature : no data available
Flammability (solid, gas) : no data available
Vapour Pressure 20°C : < 0,1 hPa
Relative vapour density at 20 °C : > 1 (air=1)
Relative density : no data available
Density : 0,84 - 0,85 kg/l
Solubility : insoluble in water.

Log Pow : > 3

Viscosity, kinematic : 100 - 200 cSt
Viscosity, dynamic : no data available
Explosive properties : no data available
Oxidising properties : no data available

30/09/2015 EN (English) 4/8

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Explosive limits : 0,6 - 7 vol %

9.2. Other information

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20'C.

### **SECTION 10: Stability and reactivity**

### Reactivity

Stable under normal conditions of use.

#### 10.2. **Chemical stability**

Stable under normal conditions.

### Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

### **Conditions to avoid**

Moisture. Overheating

#### Incompatible materials 10.5.

Strong oxidizing agents. strong acids.

### **Hazardous decomposition products**

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

### **SECTION 11: Toxicological information**

### Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

araffinic (64742-54-7)
> 5000 mg/kg
> 5000 mg/kg
> 5,53 mg/l
37-01-4)
> 5000 mg/kg
> 2000 ml/kg
> 5,2 mg/l/4h

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified Respiratory or skin sensitisation Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

ENEOS Premium Ultra S 0W-30		
Viscosity, kinematic	100 - 200 mm²/s	
Other information	: Toxicological data have not been determined specifically for this product. Information given is	

based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

### **SECTION 12: Ecological information**

### **Toxicity**

: Ecotoxicological data have not been determined specifically for this product. Information given Ecology - general

is based on a knowledge of the components and the ecotoxicology of similar products.

: This product floats on water and may affect the oxygen-balance in the water. Ecology - water

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
1-Decene, homopolymer, hydrogenated (68037-01-4)	
LC50 fish 1	> 1000 mg/l Oncorhynchus mykiss (Rainbow trout)

30/09/2015 EN (English) 5/8

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-Decene, homopolymer, hydrogenated (6803	-Decene, homopolymer, hydrogenated (68037-01-4)	
EC50 Daphnia 1	190 mg/l EC50 48h - Daphnia magna [mg/l]	
LC50 fish 2	> 750 mg/l Pimephales promelas	

### 12.2. Persistence and degradability

	ENEOS Premium Ultra S 0W-30		
-	Persistence and degradability	Not readily biodegradable.	
	1-Decene, homopolymer, hydrogenated (6803	7-01-4)	
	Persistence and degradability	Not readily biodegradable.	

### 12.3. Bioaccumulative potential

ENEOS Premium Ultra S 0W-30	
Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
1-Decene, homopolymer, hydrogenated (68037-01-4)	
Log Pow	> 3

# Bioaccumulative potential 12.4. Mobility in soil

12.4. Mobility in soil		
ENEOS Premium Ultra S 0W-30		
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.	
1-Decene, homopolymer, hydrogenated (6803	7-01-4)	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.	

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not discharge into

drains or the environment.

Additional information : Hazardous waste.

Ecology - waste materials : Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do

not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at

This product is not expected to bioaccumulate through food chains in the environment.

hazardous or special waste collection point.

European List of Waste (LoW) code : 13 02 06\* - Synthetic engine, gear and lubricating oils

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Proper Shipping Name : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

# 14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

30/09/2015 EN (English) 6/8

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

**RID** 

Transport hazard class(es) (RID) : Not applicable

Packing group

Packing group (UN) : Not applicable Packing group (IMDG) : Not applicable Packing group (IATA) : Not applicable Packing group (ADN) : Not applicable Packing group (RID) : Not applicable

**Environmental hazards** 

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

#### Special precautions for user 14.6.

### - Overland transport

no data available

### - Transport by sea

no data available

### - Air transport

no data available

# - Inland waterway transport

Not subject to ADN : No

- Rail transport

Carriage prohibited (RID) : No

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. **EU-Regulations**

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

#### **National regulations** 15.1.2.

No additional information available

### **Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out

1-Decene, homopolymer, hydrogenated

# **SECTION 16: Other information**

### Full text of R-, H- and EUH-statements:

	Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4	
Asp. Tox. 1		Aspiration hazard, Category 1	
	30/00/2015 EN	J (English)	10

30/09/2015 EN (English)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H304	May be fatal if swallowed and enters airways
H413	May cause long lasting harmful effects to aquatic life
EUH208	Contains . May produce an allergic reaction
R53	May cause long-term adverse effects in the aquatic environment

### SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

30/09/2015 EN (English) 8/8